



# Safety Data Sheet

## The Craftsman Collection

### JAVA



## 1. Identification

<b>Product identifier</b>	The Craftsman Collection JAVA		
<b>Product code</b>	CC015		
<b>Other means of identification</b>	N/Av.		
<b>Recommended use of the chemical and restrictions on use</b>	PAINT. A protective and/or decorative finish or accompanying paint product.		
<b>Manufacturer</b>	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 Tel. 1-800-262-5710 Fax 1-405-262-9310 <a href="http://www.geminicoatings.com">www.geminicoatings.com</a>		
<b>Emergency phone number</b>	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour  HAZMAT Response and MSDS help: EMI 800-510-8510		

## 2. Hazard identification

<b>Summary</b>	Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	---

### WHMIS 2015/OSHA HCS 2012/GHS



Flammable liquids (Category 3)  
 Acute toxicity, inhalation (Category 4)  
 Skin corrosion/irritation (Category 2)  
 Serious eye damage/eye irritation (Category 2)  
 Skin sensitizer (Category 1)  
 Germ cell mutagenicity (Category 1B)  
 Carcinogenicity (Category 1B)  
 Reproductive toxicity (Category 1B)  
 Specific target organ toxicity, repeated exposure (Category 1)  
 Aspiration hazard (Category 1)

**Other hazards which do not result in classification :**  
 Acute toxicity, dermal (Category 5)

### DANGER

H226: Flammable liquid and vapour  
 H350: May cause cancer  
 H340: May cause genetic defects  
 H360: May damage fertility or the unborn child  
 H372: Causes damage to the central nervous system through prolonged or repeated exposure by inhalation  
 H304: May be fatal if swallowed and enters airways

H332: Harmful if inhaled  
H319: Causes serious eye irritation  
H315: Causes skin irritation  
H317: May cause an allergic skin reaction  
H313: May be harmful in contact with skin  
P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground or bond container and receiving equipment.  
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe mist, vapours and spray.  
P264: Wash skin thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only in a well-ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves, protective clothing and eye protection.  
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.  
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical advice or attention.  
P308+313: IF exposed or concerned: Get medical advice/attention.  
P321: Specific treatment (see section 4 of SDS or on this label).  
P362+364: Take off contaminated clothing and wash before reuse.  
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.  
P403+235: Store in a well ventilated place. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

### 3. Composition/information on ingredients

Common name	CAS	Weight % content
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	38 - 39 %
Stoddard solvent (Mineral Spirits)	8052-41-3	30 - 31 %
2-Butoxyethanol	111-76-2	4.5 - 5.5 %
Iron (III) Oxide	1309-37-1	3.5 - 4.5 %
Naphthalene	91-20-3	3.5 - 4.5 %
1,2,4-Trimethylbenzene	95-63-6	1.5 - 2.5 %
Synthetic Amorphous Fumed Silica	112945-52-5	1.5 - 2.5 %
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	1 - 2 %
Carbon black	1333-86-4	0.5 - 1.5 %
Xylene	1330-20-7	0.1 - 1 %

## 4. First-aid measures

<b>Inhalation</b>	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
<b>Skin contact</b>	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
<b>Eye contact</b>	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
<b>Ingestion</b>	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious rinse mouth with water and give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
<b>Other</b>	No information available.
<b>Symptoms</b>	May cause irritation to skin and eyes. May cause an allergic reaction of the skin. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
<b>Notes to the physician</b>	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO <sub>2</sub> ). Do not use direct water jet.
<b>Specific hazards arising from the chemical</b>	Flammable liquid and vapours. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
<b>Special protective equipment</b>	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
<b>Special protective actions for fire-fighters</b>	Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
<b>Environmental precautions</b>	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
<b>Methods and materials for containment and cleaning up</b>	Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite, Dustbane) and place in an appropriate waste disposal clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
<b>Conditions for safe storage, including any incompatibilities</b>	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).
<b>Storage temperature</b>	10 to 25°C (50 to 77°F)

## 8. Exposure controls/personal protection

<b>Immediately Dangerous to Life or Health</b>	Stoddard solvent (Mineral Spirits): 20000 mg/m <sup>3</sup> . 2-Butoxyethanol: 700 ppm. Naphthalene: 250 ppm. Iron (III) Oxide: 2500 mg/m <sup>3</sup> , value as iron. Carbon Black: 1750 mg/m <sup>3</sup> . Synthetic Amorphous Fumed Silica: 3000 mg/m <sup>3</sup> . Xylenes: 900 ppm.		
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m <sup>3</sup>	BC
	TWA (8h)	290 mg/m <sup>3</sup>	BC
		100 ppm	525 mg/m <sup>3</sup> ACGIH , ON, RSST
		500 ppm	2900 mg/m <sup>3</sup> OSHA
2-Butoxyethanol	TWA (8h)	20 ppm	ACGIH , BC, ON
		20 ppm	97 mg/m <sup>3</sup> RSST
		50 ppm	240 mg/m <sup>3</sup> OSHA
Iron (III) Oxide	TWA (8h) Respirable Dust	5 mg/m <sup>3</sup>	ACGIH , BC, ON, RSST
	Fume and Dust	10 mg/m <sup>3</sup>	OSHA
Naphthalene	STEL	15 ppm	BC
		15 ppm	78 mg/m <sup>3</sup> ON
		15 ppm	79 mg/m <sup>3</sup> ACGIH , RSST
	TWA (8h)	10 ppm	BC , OSHA
		10 ppm	52 mg/m <sup>3</sup> ACGIH , ON, RSST
1,2,4-Trimethylbenzene	TWA (8h)	25 ppm	ACGIH , BC, ON, OSHA
		25 ppm	123 mg/m <sup>3</sup> RSST
Synthetic Amorphous Fumed Silica	TWA (8h) Respirable Dust	1.5 mg/m <sup>3</sup>	BC
	Respirable Dust	3 mg/m <sup>3</sup>	ACGIH , ON
	Total Dust	4 mg/m <sup>3</sup>	BC
	Respirable Dust	6 mg/m <sup>3</sup>	RSST
	Total Dust	10 mg/m <sup>3</sup>	ACGIH , ON
Naphtha (petroleum), hydrotreated heavy (C6-C13)	TWA (8h) Mist	5 mg/m <sup>3</sup>	ACGIH , RSST
		175 ppm	1200 mg/m <sup>3</sup> Other

Carbon black	Ceiling	300 ppm	OSHA
	TWA (8h)	3.5 mg/m <sup>3</sup> 3 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup>	OSHA ACGIH , BC, ON RSST
Xylene	STEL	150 ppm	ACGIH , BC, ON, OSHA
	TWA (8h)	150 ppm 651 mg/m <sup>3</sup>	RSST
		100 ppm 100 ppm 434 mg/m <sup>3</sup>	ACGIH , BC, ON, OSHA RSST
<b>Appropriate engineering controls</b>	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.		
<b>Individual protection measures</b>			
<b>Eye</b>	Wear chemical splash goggles.		
<b>Hands</b>	Wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.		
<b>Skin</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear synthetic apron, if necessary, to prevent repeated or prolonged contact with skin.		
<b>Respiratory</b>	Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.		
<b>Feet</b>	Wear rubber boots to clean up a spill.		

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid	<b>Flammability</b>	Flammable
<b>Colour</b>	Brown espresso	<b>Flammability limits</b>	N/Av.
<b>Odour</b>	Solvent	<b>Flash point</b>	42°C (107.6°F)
<b>Odour threshold</b>	N/Av.	<b>Auto-ignition temperature</b>	226°C (438.8°F)
<b>pH</b>	N/Av.	<b>Sensibility to electrostatic charges</b>	Yes
<b>Melting point</b>	N/Av.	<b>Sensibility to sparks and/or friction</b>	N/Av.
<b>Freezing point</b>	N/Av.	<b>Vapour density</b>	>1 (Air = 1)
<b>Boiling point</b>	150°C (302°F)	<b>Relative density</b>	0.916 kg/L (Water = 1)
<b>Solubility</b>	Negligible (<2%) in water	<b>Partition coefficient n-octanol/water</b>	N/Av.
<b>Evaporation rate</b>	> Butyl Acetate	<b>Decomposition temperature</b>	N/Av.
<b>Vapour pressure</b>	N/Av.	<b>Viscosity</b>	N/Av.

<b>Percent Volatile</b>	89.5%	<b>Molecular mass</b>	N/Ap.
N/Av.: Not Available    N/Ap.: Not Applicable    Und.: Undetermined    N/E: Not Established			

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions (including polymerizations)</b>	A dangerous reaction will not occur.
<b>Conditions to avoid</b>	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidants, strong bases, mineral acids, strong acids.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information


<b>Numerical measures of toxicity</b>	Solvent naphtha (petroleum), heavy aromatic (C9-C16)	Ingestion	7050 mg/kg	Rat	LD50
		Inhalation	>5.2 mg/l/4h	Rat	LC50
		Skin	>2000 mg/kg	Rat	LD50
	Stoddard solvent (Mineral Spirits)	Ingestion	>5000 mg/kg	Rat	LD50
		Inhalation	>12 mg/l/4h	Rat	LC50
		Skin	>3000 mg/kg	Rabbit	LD50
	2-Butoxyethanol	Ingestion	560 mg/kg	Rat	LD50
		Inhalation	2.21 mg/l/4h	Rat	LC50
		Skin	220 mg/kg	Rabbit	LD50
	Naphthalene	Ingestion	490 mg/kg	Rat	LD50
		Inhalation	>1 mg/l/1h	Rat	LC50
		Skin	1120 mg/kg	Rabbit	LD50
	Iron (III) Oxide	Ingestion	>10000 mg/kg	Rat	LD50
		Skin	>2000 mg/kg	Rabbit	LD50
	1,2,4-Trimethylbenzene	Ingestion	5000 mg/kg	Rat	LD50
		Inhalation	18 mg/l/4h	Rat	LC50
	Skin	>3160 mg/kg	Rabbit	LD50	
Synthetic Amorphous Fumed Silica	Ingestion	>5000 mg/kg	Rat	LD50	
	Inhalation	>2.08 mg/l/4h	Rat	LC50	
	Skin	>5000 mg/kg	Rabbit	LD50	
Naphtha (petroleum), hydrotreated heavy (C6-C13)	Ingestion	>10000 mg/kg	Rat	LD50	
	Inhalation	>8.5 mg/l/4h	Rat	LC50	
	Skin	>3200 mg/kg	Rabbit	LD50	
Carbon black	Ingestion	>15400 mg/kg	Rat	LD50	
	Skin	>3000 mg/kg	Rabbit	LD50	
Xylene	Ingestion	3523 mg/kg	Rat	LD50	
	Inhalation	27.6 mg/l/4h	Rat	LC50	
	Skin	3200 mg/kg	Rabbit	LD50	
<b>Likely routes of exposure</b>	Skin, eyes, inhalation, ingestion.				

<p><b>Delayed, immediate and chronic effects</b></p>	<p><b>Eye contact</b> May cause irritation, redness, tearing and blurred vision. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to irritating results.</p> <p><b>Skin contact</b> May cause redness, dryness or rash of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.</p> <p><b>Inhalation</b> Excessive inhalation is harmful. May cause irritation to nose, throat and respiratory tract. The severity of symptoms may vary depending on exposure conditions. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Numerous studies on human, especially from the monitoring of painters, suggest that long-term occupational exposure to white spirit (all types) cause chronic toxic encephalopathy (adverse central nervous system effects).</p> <p><b>Ingestion</b> Harmful or fatal if inhaled into the lungs (ingestion/vomiting). Contains a substance that can cause target organ damage, according to data obtained on animals. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.</p> <p><b>Respiratory or skin sensitization</b> There is a case of dermatitis allergy to naphthalene reported in human. However, there is a report of negative results in 2 guinea pig skin sensitizing tests (OECD Guideline 406).</p> <p><b>IARC/NTP Classification</b> <b>Common name IARC NTP</b>  Naphthalene 2B R  Carbon black 2B -  IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic.  NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p> <p><b>Carcinogenicity</b> Many carcinogenicity Studies with solvent naphtha (petroleum) products containing no significant concentrations of known carcinogens compounds (&lt;0.1%) have shown dermal tumours developed. It was concluded that these middle distillate petroleum product are potential skin carcinogens (OECD Guideline 451). Contains substances that can cause cancer based on animal data. The risk of cancer depends on duration and level of exposure.</p> <p><b>Mutagenicity</b> Some solvent naphtha (petroleum) products are considered mutagenic in bacterial assay (OECD Guideline 471).</p> <p><b>Reproductive toxicity</b> Xylene overexposure may affect fetal development in laboratory animals by inhalation during pregnancy. The inhalation of high concentration of 2-Butoxyethanol has an embryotoxic and/or foetotoxic effect on rats and rabbits at doses which were severely toxic to the animals</p> <p><b>Specific target organ toxicity - single exposure</b> No target organ is listed.</p> <p><b>Specific target organ toxicity - repeated exposure</b> Central nervous system.</p>
<p><b>Interactive effects</b></p>	<p>No information available for this product.</p>
<p><b>Other information</b></p>	<p>The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg but lower than 5000 mg/Kg. These values are classified category 5 by the GHS. These values are not classified according to WHMIS 2015 and OSHA HCS 2012. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 10 mg/L/4h but lower than 20 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4).</p>


## 12. Ecological information

<b>Ecological toxicity</b>	Oncorhynchus mykiss LC50 2.34 mg/L - 96 h (Solvent naphtha (petroleum), heavy aromatic (C9-C16))* Daphnia magna EC50 0.95 mg/L - 48 h (Solvent naphtha (petroleum), heavy aromatic (C9-C16))* Oncorhynchus mykiss LC50 0.91-2.82 mg/L - 96 h (naphthlene)* Daphnia magna EC50 1.09-3.4 mg/L - 48 h (naphthlene)* Pimephales promelas LC50 7.19-8.28 mg/L - 96 h (1,2,4-trimethylbenzene)* Daphnia magna EC50 6.14 mg/L - 48 h (1,2,4-trimethylbenzene)*
<b>Persistence</b>	The product contains components that may persist in the environment.
<b>Degradability</b>	No information available for this product. The product is a heavy hydrocarbon mixture in which some ingredients are not expected to be readily biodegradable (OECD 301). Stoddard solvent (Mineral Spirits) is not rapidly degrading, according to Biochemical Oxygen Demand (BOD) of 12-13% (EHC187, 1996). 2-Butoxyethanol is readily biodegradable 90.4% in 28 days (OECD Guideline 301B). Naphthalene is considered to be not readily biodegradable, but is inherently or easily biodegradable under aerobic conditions in many non-standard tests. 1,2,4-Trimethylbenzene is not readily biodegradable (4 to 18% in 28 days) according to OECD 301C Guideline.
<b>Bioaccumulative potential</b>	No information available for this product. The product is a mixture of heavy hydrocarbon which some ingredients may be bioaccumulative. 2-Butoxyethanol is not expected to bioaccumulate based on a low partition coefficient (Log Kow <2). Naphthalene exhibits a low potential of accumulation with a Bioconcentration Factors (BCF) of <200 (OECD Guideline 305).
<b>Mobility in soil</b>	No information available for this product. The product is a hydrocarbon mixture of which some ingredients can evaporate into the air while others present a medium to low mobility in soil. The estimated Koc value of 0.83 suggests that 2-Butoxyethanol is expected to have high mobility in soil (TOXNET). The Koc values of <650 suggest that naphthalene is expected to have high to no mobility in soil (TOXNET).
<b>Other adverse effects</b>	This chemical does not deplete the ozone layer. Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers. *Data from Gemini Coatings safety data sheet.

## 13. Disposal considerations

<b>Container</b> 	Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. DO NOT puncture, cut, heat or burn container, even after use. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
--	---

## 14. Transport information

<b>UN Number</b>	UN 1263
<b>UN Proper Shipping Name</b>	PAINT
<b>Environmental hazards</b>	Contains an ingredient which is a marine pollutant.
<b>Special precautions for user</b>	Permit required for transportation with proper placards displayed on vehicle.
<b>TDG - Transportation of Dangerous Goods (Canada)</b>	
<b>Transport hazard class(es)</b>	 Class 3



<b>Packing group</b>	III
<b>IMO/IMDG - International Maritime Transport</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG III. Emergency schedules (EmS-No) F-E, S-E
<b>IATA - International Air Transport Association</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG III.
These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.	

## 15. Regulatory information

### CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	X	X		X
Stoddard solvent (Mineral Spirits)	8052-41-3	X	X		X
2-Butoxyethanol	111-76-2	X	X		X
Iron (III) Oxide	1309-37-1		X		
Naphthalene	91-20-3	X	X		X
1,2,4-Trimethylbenzene	95-63-6	X	X		X
Synthetic Amorphous Fumed Silica	112945-52-5		X		
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X	X		X
Carbon black	1333-86-4		X		
Xylene	1330-20-7	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

### UNITED STATE OF AMERICA

Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	X								
Stoddard solvent (Mineral Spirits)	8052-41-3	X								
2-Butoxyethanol	111-76-2	X								
Iron (III) Oxide	1309-37-1	X								
Naphthalene	91-20-3	X	X	X		X	X		X	X
1,2,4-Trimethylbenzene	95-63-6	X		X	X					
Synthetic Amorphous Fumed Silica	112945-52-5	X								
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X								
Carbon black	1333-86-4	X								
Xylene	1330-20-7	X	X	X		X	X		X	

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant

- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

### California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Naphthalene	91-20-3	X	
Carbon black	1333-86-4	X	

### Other regulations

#### WHMIS 1988



B3 D1A D2A D2B

Class B3 : Combustible Liquid

Class D1A : Very toxic material causing immediate and serious toxic effects

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

#### HMIS



#### NFPA



## 16. Other information

<b>Date</b> (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-02-09
<b>Version</b>	02
<b>Other information</b>	<p>REFERENCES:</p> <ul style="list-style-type: none"> <li>- Original safety data sheet (product code CC015) from Gemini Coatings. Date prepared: 2015-10-20.</li> <li>- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, <a href="http://hazmap.nlm.nih.gov/index.php">http://hazmap.nlm.nih.gov/index.php</a></li> <li>- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, <a href="http://toxnet.nlm.nih.gov/">http://toxnet.nlm.nih.gov/</a></li> <li>- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <a href="http://www.reptox.csst.qc.ca">http://www.reptox.csst.qc.ca</a></li> <li>- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <a href="http://www.cdc.gov/niosh/npg/npg.html">http://www.cdc.gov/niosh/npg/npg.html</a></li> <li>- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <a href="http://www.inchem.org">http://www.inchem.org</a></li> <li>- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, <a href="http://webnet.oecd.org/HPV/UI/Search.aspx">http://webnet.oecd.org/HPV/UI/Search.aspx</a></li> </ul> <p>DATE OF FIRST VERSION OF SDS: 2015-12-09</p> <p>CHANGES MADE IN THE VERSION 02: sections 2, 3, 8, 9, 11, and 12.</p> <p>ACGIH: American Conference of Governmental Industrial Hygienists</p>

AIHA: American Industrial Hygiene Association  
HMIS: Hazardous Materials Identification System  
NFPA: National Fire Protection Association  
OSHA: Occupational Safety and Health Administration (USA)  
NIOSH: National Institute for Occupational Safety and Health  
NTP: National Toxicology Program  
RSST: Règlement sur la santé et la sécurité du travail (Québec)  
GHS: Globally Harmonized System  
IARC: International Agency for Research on Cancer  
IDLH: Immediately Dangerous to Life or Health  
STEL: Short Term Exposure Limit (15 min)  
TWA: Time Weighted Averages  
WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.