



# SAFETY DATA SHEET

## SECTION 1 - Chemical Product and Company Information

Product Name: WB IMPREG DARK CHESTNUT STAIN Product Code: TWP-9066

Manufactured by:  
**Gemini Coatings**  
 2300 Holloway Drive  
 El Reno, OK 73036  
 800-262-5710

**24- Hour Emergency (Spill, Leak, Exposure or Accident):**  
**INFOTRAC 800-535-5053**  
**Outside USA, Call Collect 1-352-323-3500**

**24- Hour Emergency HAZMAT Response and MSDS Help:**  
**EMI 800-510-8510**

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label .

## SECTION 2 - Hazards Identification

### GHS Ratings:

Oral Toxicity	Acute Tox. 3	Oral>50+<=300mg/kg
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Skin sensitizer	1	Skin sensitizer

### GHS Hazards

H302	Harmful if swallowed
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

### GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash any exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment (see First Aid section on this label)
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P405	Store locked up

**Signal Word: Warning****SECTION 3 - Composition/Information on Ingredients**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Diethylene glycol monoethyl ether 111-90-0 3%			
3-Iodo-2-propynyl butylcarbamate 55406-53-6 2%			
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) 1309-37-1 1%	10 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust, listed under Rouge); 5 mg/m <sup>3</sup> TWA (respirable fraction, listed under Rouge)	5 mg/m <sup>3</sup> TWA (respirable particulate matter)	NIOSH: 5 mg/m <sup>3</sup> TWA (dust and fume, as Fe)

**SECTION 4 - First Aid Measures****Inhalation:**

Remove exposed individual to fresh air and assist breathing if necessary. Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

**Eye Contact:**

Direct contact may cause eye irritation. Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

**Skin:**

Irritating to the skin on repeated or prolonged contact. Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

**Ingestion:**

Can cause gastrointestinal irritation. Rinse mouth out immediately. DO NOT induce vomiting. Contact physician or poison control center immediately.

**SECTION 5 - Fire Fighting Measures**

Alcohol Foam, CO<sub>2</sub>, Dry Chemical

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product.

Dried finish can burn, giving off oxides of carbon.

None known. However, fire fighters should wear self-contained breathing apparatus to avoid inhalation if material is involved in a general fire.

**SECTION 6 - Accidental Release Measures**

Keep out of sewers. Dike spill area and add absorbent earth, sand or sawdust to spilled liquid. Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. DO NOT incinerate closed containers. Incinerate in approved facilities. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned and destroyed.

**SECTION 7- Handling and Storage**

**Handling:**

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

\*\* Keep temperature above 32 Degrees F.

**Storage:**

Keep containers tightly closed when not in use. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas. KEEP FROM FREEZING.

**SECTION 8 - Exposure Controls/Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Diethylene glycol monoethyl ether 111-90-0			
3-Iodo-2-propynyl butylcarbamate 55406-53-6			
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) 1309-37-1	10 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust, listed under Rouge); 5 mg/m <sup>3</sup> TWA (respirable fraction, listed under Rouge)	5 mg/m <sup>3</sup> TWA (respirable particulate matter)	NIOSH: 5 mg/m <sup>3</sup> TWA (dust and fume, as Fe)

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits. Avoid prolonged or repeated breathing of vapors.

**Respiratory Protection:**

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

**Skin Protection:**

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

**Eye Protection:**

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes. Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended.

**Hygienic Practices**

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

**SECTION 9 - Physical and Chemical Properties**

<p><b>Vapor Density</b> Heavier Than Air</p> <p><b>Boiling range:</b> 100 - 196°C</p> <p><b>Freezing point:</b> N/A</p> <p><b>Flammability:</b> N/A</p> <p><b>Autoignition temperature:</b> 204°C</p> <p><b>Relative Density:</b> N/A</p>	<p><b>Evaporation Rate</b> Slower than Butyl Acetate</p> <p><b>Melting point:</b> N/A</p> <p><b>Flash point:</b> 999°F, 999°C</p> <p><b>Explosive Limits:</b> N/A</p> <p><b>Decomposition temperature:</b> N/A</p> <p><b>Vapor Pressure</b> N/A</p>
---	---

<p><b>Odor threshold:</b> N/A</p> <p><b>SPECIFIC GRAVITY</b> 1.0315</p> <p><b>Partition coefficient (n- N/A octanol/water):</b></p> <p><b>Grams VOC less water:</b> N/A</p> <p><b>% WT. VOLATILE (VOC)</b> 2.6478</p> <p><b>Lbs VOC/Gallon Solids</b> 1.9453</p> <p><b>SOLIDS VOL%</b> 11.6909</p> <p><b>SPREAD @ 1 MIL</b> 187.5213</p> <p><b>Appearance</b> Colored Liquid</p> <p><b>Physical State</b> Liquid</p> <p><b>Coating VOC (g/l)</b> 188.5646</p> <p><b>Coating VOC (Lb/Gl)</b> 1.5736</p>	<p><b>pH:</b> N/A</p> <p><b>Solubility:</b> N/A</p> <p><b>Viscosity:</b> N/A</p> <p><b>% VOLUME VOLATILE (VOC)</b> 2.7618</p> <p><b>% Pig. by wt.</b> 2.2680</p> <p><b>VOLATILE WT%</b> 85.5979</p> <p><b>DENSITY (Lb/Gal)</b> 8.5893</p> <p><b>HAPS (lbs/gl)</b> 0.0000</p> <p><b>Odor</b> N/A</p> <p><b>Material VOC (g/l)</b> 27.2525</p> <p><b>Material VOC (Lb/Gl)</b> 0.2274</p>
--	--

**SECTION 10 - Stability and Reactivity**

**Stability:** Stable under normal conditions.

**Materials to Avoid:** None known.

**Conditions to avoid:** Excessive heat, poor ventilation, excessive aging.

**Hazardous Decomposition:** Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

Hazardous polymerization will not occur.

**SECTION 11 - Toxicological Information**

**Mixture Toxicity**

Oral Toxicity LD50: 112mg/kg  
 Inhalation Toxicity LC50: 47mg/L

**Component Toxicity**

55406-53-6      3-Iodo-2-propynyl butylcarbamate  
 Oral LD50: 1,470 mg/kg (Rat)    Dermal LD50: 2,000 mg/kg (Rat)    Inhalation LC50: 1 mg/L (Rat)

**Primary Routes of Entry:** Inhalation, Skin Contact, Eyes, Ingestion

**Skin:**

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

**Ingestion:**

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

**Inhalation:**

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea . Breathing high vapor concentrations may produce narcosis. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal.

**Eyes:**

Can cause irritation, redness, tearing and blurred vision.

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing) .

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

### SECTION 12 - Ecological Information

**Ecological Information:**

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers .

**Component Ecotoxicity**

Diethylene glycol monoethyl ether	LC50 96 h Lepomis macrochirus 10000 mg/L [static] (EPA); LC50 96 h Lepomis macrochirus 19100 - 23900 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 11400 - 15700 mg/L [flow-through] (EPA); LC50 96 h Pimephales promelas 11600 - 16700 mg/L [flow-through] (EPA) EC50 48 h Daphnia magna 3940 - 4670 mg/L (IUCLID)
3-Iodo-2-propynyl butylcarbamate	LC50 96 h Lepomis macrochirus 0.14 - 0.32 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 0.049 - 0.079 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 0.05 - 0.089 mg/L (EPA); LC50 96 h Pimephales promelas 0.18 - 0.23 mg/L [flow-through] (EPA)
Iron oxide (Fe2O3)	LC50 96 h Danio rerio 100000 mg/L [static] (approximately, ECHA)

### SECTION 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

### SECTION 14 - Transportation Information

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	NOT REGULATED			
	<b>Freight Class:</b>			

### SECTION 15 - Regulatory Information

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	<input type="text" value="0"/>	<b>HMIS &amp; NFPA Hazard Rating</b> <b>Legend</b> * = Chronic Health Hazard <b>0 = INSIGNIFICANT</b> <b>1 = SLIGHT</b> <b>2 = MODERATE</b> <b>3 = HIGH</b>
<b>FLAMMABILITY</b>	<input type="text" value="0"/>	
<b>PHYSICAL HAZARD</b>	<input type="text" value="0"/>	
<b>PERSONAL PROTECTION</b>	<input type="text"/>	

### SECTION 16 - Disclaimer

Date Prepared: 5/29/2025

Date revised: 2024-03-08

Reviewer Revision

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS

LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.