



# SAFETY DATA SHEET

**WPC-01**

**RADCON 100 CLEAR**

4/21/2026

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product Identifier

WPC-01

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information). Not recommended for any other use not detailed on product data sheet or label.

### 1.3 Details of the supplier of the safety data sheet

**GEMINI COATINGS INC. (WEST BLDG)**  
2300 SW HOLLOWAY ST  
El Reno, OK 730365773 US  
(800) 262-5710  
[www.gemini-coatings.com](http://www.gemini-coatings.com)

### 1.4 Emergency telephone number

INFOTRAC 800-535-5053 USA Only  
352-323-3500 International (Outside of USA)

## SECTION 2: Hazards Identification

### 2.1 Classification of the substance or mixture

Acute Tox. 3; Carc. 1; Flam. Liq. 2; Muta. 1; Repr. 1; STOT RE 2

### 2.2 Label elements



Flammable

Toxic

Health Hazard

Danger

H225-Highly flammable liquid and vapour.

H331-Toxic if inhaled.

H340-May cause genetic defects.

H350-May cause cancer.

H360-May damage fertility or the unborn child.

H373-May cause damage to organs through prolonged or repeated exposure.

# WPC-01

## RADCON 100 CLEAR

4/21/2026

---

### Prevention

- P201-Obtain special instructions before use.
- P210-Keep away from heat, sparks, open flames, and other ignition sources. No smoking.
- P240-Ground/bond container and receiving equipment.
- P241-Use explosion-proof electrical/ventilating/lighting/and all material-handling equipment.
- P242-Use only non-sparking tools.
- P243-Take precautionary measures against static discharge.
- P260-Do not breathe dust/fume/gas/mist/vapours/spray.
- P261-Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271-Use only outdoors or in a well-ventilated area.
- P280-Wear protective gloves/protective clothing/eye protection/face protection.

### Response

- P303+P361+P353-IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
- P304+P340-IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
- P311-Call a POISON CENTER or doctor/physician.
- P314-Get medical advice/attention if you feel unwell.
- P321-Specific treatment (see First Aid section on this label)
- P370+P378-In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.

### Storage

- P403+P233-Store in a well-ventilated place. Keep container tightly closed.
- P403+P235-Store in a well-ventilated place. Keep cool.
- P405-Store locked up.

### Disposal

- P501-Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

## 2.3 Other hazards

## 2.4 Unknown Acute Toxicity (US)

# SECTION 3: Composition/information on ingredients

## 3.1 Substances

# WPC-01

## RADCON 100 CLEAR

4/21/2026

### 3.2 Mixtures

| Chemical Name                                | CAS Number                | Percentage            | Classification   |
|--|---------------------------|-----------------------|--|
| Hydrocarbon waxes, petroleum,<br>PROPRIETARY | 64742-42-3<br>PROPRIETARY | 5% - 10%<br>45% - 70% | Aquatic Chronic 4  |
| Chlorothalonil                               | 1897-45-6                 | 1% - 5%               | Aquatic Acute 1 Aquatic Chronic 1 Carc.<br>2 Eye Corr. 1 Resp. Sens. 1A Skin<br>Sens. 1 STOT RE 2 STOT SE  |
| Petroleum distillates, hydrotr               | 64742-47-8                | 10% - 30%             | Aquatic Acute 2 Aquatic Chronic 2 Asp.<br>Tox. 1 Flam. Liq. 4  |
| Carbendazim                                  | 10605-21-7                | 0.1% - 1%             | Aquatic Acute 1 Aquatic Chronic 1 Muta.<br>1B Repr. 1B Skin Sens. 1 STOT RE 2<br>STOT SE 2                 |
| Propanol, 1(or 2)-(2-methoxyme               | 34590-94-8                | 0.1% - 1%             | Eye Irrit. 2B Flam. Liq. 4 STOT SE 3   |
| 2-Butanone, oxime                            | 96-29-7                   | 0.1% - 1%             | Aquatic Acute 3 Aquatic Chronic 3 Carc.<br>1B Skin Irrit. 2 Eye Corr. 1 Flam. Liq. 3<br>Skin Sens. 1 STOT  |
| 3-Iodo-2-propynyl butylcarbama               | 55406-53-6                | 0.1% - 1%             | Aquatic Acute 1 Aquatic Chronic 1 Skin<br>Irrit. 2 Eye Corr. 1 Skin Sens. 1 STOT<br>RE 1 STOT SE 1         |
| Carbonic acid, calcium salt (1               | 471-34-1                  | 0.1% - 1%             |  |
| Hexanoic acid, 2-ethyl-, cobal               | 136-52-7                  | Less than 0.1%        | Aquatic Acute 1 Aquatic Chronic 2 Carc.<br>1B Eye Irrit. 2A Repr. 1B Resp. Sens. 1<br>Skin Sens. 1 STOT RE |
| Calcium 2-ethylhexanoate                     | 136-51-6                  | Less than 0.1%        | Eye Corr. 1 Repr. 2  |
| Calcium propionate                           | 4075-81-4                 | Less than 0.1%        | Eye Corr. 1  |

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

#### After inhalation

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention.

#### After skin contact

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

#### After eye contact

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

#### After ingestion

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

#### Self-protection of the first aider

### 4.2 Most important symptoms and effects, both acute and delayed

### 4.3 Indication of any immediate medical attention and special treatment needed

# WPC-01

## RADCON 100 CLEAR

4/21/2026

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Alcohol Foam, CO2, Dry Chemical

##### Unsuitable extinguishing media

#### 5.2 Special hazards arising from the substance or mixture

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

\*\* Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

Oxidation may produce carbon and nitrogen oxides.

#### 5.3 Advice for firefighters

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

Use the National Fire Protection Association Class B extinguisher.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.2 Environmental precautions

#### 6.3 Methods and material for containment and cleaning up

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

\*\* Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

#### 6.4 Reference to other sections

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

\*\* Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

#### 7.3 Incompatibilities/Specific end uses(s)

##### Incompatibilities

##### Specific end use(s)

### SECTION 8: Exposure controls/personal protection

# WPC-01

## RADCON 100 CLEAR

4/21/2026

### 8.1 Control parameters

#### Propanol, 1(or 2)-(2-methoxyme(34590-94-8)

|           |           |
|-----------|-----------|
| OSHA PEL  | 600 mg/m3 |
| OSHA PEL  | 100 ppm   |
| ACGIH TLV | 50 ppm    |
| NIOSH     | 100 ppm   |
| NIOSH     | 600 mg/m3 |
| QUEBEC    | 606 mg/m3 |
| QUEBEC    | 100 ppm   |
| ONTARIO   | 100 ppm   |

#### Carbonic acid, calcium salt (1(471-34-1)

|        |          |
|--------|----------|
| QUEBEC | 10 mg/m3 |
| NIOSH  | 5 mg/m3  |
| NIOSH  | 10 mg/m3 |

### 8.2 Engineering Controls/Exposure Controls

**Engineering controls** Avoid prolonged or repeated breathing of vapors.

**Environmental exposure controls** Use local exhaust as required to control vapor concentrations.

### 8.3 Protective Measures

**Eye/face protection** Wear splash proof goggles and face shield if there is a likelihood of contact with eyes.

**Hand protection** Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile.

**Other Skin protection** An apron should be worn to avoid skin contact.

**Other protection**

**Respiratory protection** If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

**General hygiene consideration** Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

**Thermal hazards**

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                          |         |                                |             |
|--------------------------|---------|--------------------------------|-------------|
| Autoignition Temp        | 0.00 °C | Coating VOC Lbs/Gal            | 1.34        |
| Coating VOC grams/liter  | 161.14  | Densities                      | 8.1565      |
| Density                  | 0       | Flash Points                   | 65.00 °C    |
| Lbs HAPs / Gallon        | 0.01    | Material VOC Lbs/Gal           | 1.34        |
| Material VOC grams/liter | 161.14  | Physical State                 | LIQUID      |
| Solids Vol%              | 79.53   | Specific Gravity               | 0.978       |
| State of Matter          | Liquid  | Upper/lower flammability range | 0 - 0 vol % |
| Weight of VOC            | 134.48  |                                |             |

### 9.2 Other information

**SECTION 10: Stability and Reactivity**

**10.1 Reactivity**

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

**10.4 Conditions to avoid**

Strong oxidizing agents, strong alkalines, strong mineral acids.

high heat, sparks, flames, static discharge.

\*\* Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored an/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

**10.5 Incompatible materials**

Strong oxidizing agents, strong alkalines, strong mineral acids.

**10.6 Hazardous decomposition products**

Oxidation may produce carbon and nitrogen oxides.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Skin contact**

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

**Eye contact**

Can cause irritation, redness, tearing and blurred vision.

**Inhalation**

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness and even asphyxiation. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**Ingestion**

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

**Symptoms related to characteristicstics**

**Acute effects**

**Chronic effects**

**Numerical measures of Toxicity**

# WPC-01

## RADCON 100 CLEAR

4/21/2026

### Carbendazim (10605-21-7)

|                    |                                    |          |
|--------------------|------------------------------------|----------|
| LD50 Dermal RABBIT | > 10000 mg/kg test substance admin | NLM_HSDB |
| LD50 Ingestion RAT | > 5050 mg/kg no deaths occurred    | CHEMVIEW |

### Calcium 2-ethylhexanoate (136-51-6)

|                     |                               |          |
|---------------------|-------------------------------|----------|
| LD50 Ingestion RAT  | 300 - 2000 mg/kg              | ECHA_API |
| LC50 Inhalation RAT | > 4.8 mg/L no deaths occurred | CHEMVIEW |

### Hexanoic acid, 2-ethyl-, cobal (136-52-7)

|                     |                                     |          |
|---------------------|-------------------------------------|----------|
| LC50 Inhalation RAT | > 10 mg/L cobalt octoate 12% prepar | CHEMVIEW |
| LD50 Dermal RABBIT  | > 5000 mg/kg no deaths occurred     | CHEMVIEW |
| LD50 Ingestion RAT  | = 3129 mg/kg                        | ECHA_API |

### Chlorothalonil (1897-45-6)

|                     |                                 |           |
|---------------------|---------------------------------|-----------|
| LD50 Ingestion RAT  | > 5000 mg/kg no deaths occurred | ECHA      |
| LD50 Dermal RABBIT  | > 10 g/kg                       | NLM_CIP   |
| LC50 Inhalation RAT | = 0.1 mg/L                      | JAPAN_GHS |

### Propanol, 1(or 2)-(2-methoxyme (34590-94-8)

|                    |              |          |
|--------------------|--------------|----------|
| LD50 Dermal RABBIT | = 9500 mg/kg | NLM_CIP  |
| LD50 Ingestion RAT | = 5.35 g/kg  | NLM_HSDB |

### Calcium propionate (4075-81-4)

|                     |                                      |         |
|---------------------|--------------------------------------|---------|
| LD50 Ingestion RAT  | = 3920 mg/kg                         | NLM_CIP |
| LD50 Dermal RABBIT  | = 500 mg/kg                          | IUCLID  |
| LC50 Inhalation RAT | > 19.7 mg/L death occurred (1 out of | ECHA    |

### Carbonic acid, calcium salt (1 (471-34-1)

|                     |                             |          |
|---------------------|-----------------------------|----------|
| LC50 Inhalation RAT | > 3 mg/L no deaths occurred | ECHA_API |
| LD50 Dermal RAT     | > 2000 mg/kg                | ECHA_API |
| LD50 Ingestion RAT  | = 6450 mg/kg                | NLM_CIP  |

### 3-Iodo-2-propynyl butylcarbama (55406-53-6)

|                     |                                 |        |
|---------------------|---------------------------------|--------|
| LD50 Ingestion RAT  | = 1470 mg/kg in corn oil        | EPA_HP |
| LD50 Dermal RAT     | > 2000 mg/kg no deaths occurred | EU_CLH |
| LC50 Inhalation RAT | = 0.23 mg/L                     | EU_CLH |

### Hydrocarbon waxes, petroleum, (64742-42-3)

|                    |                                       |          |
|--------------------|---------------------------------------|----------|
| LD50 Dermal RABBIT | > 3600 mg/kg                          | NLM_CIP  |
| LD50 Ingestion RAT | > 5000 mg/kg in arachis oil; no death | CHEMVIEW |

### Petroleum distillates, hydrotr (64742-47-8)

|                     |              |         |
|---------------------|--------------|---------|
| LD50 Ingestion RAT  | > 5000 mg/kg | IUCLID  |
| LD50 Dermal RABBIT  | > 2000 mg/kg | NLM_CIP |
| LC50 Inhalation RAT | > 5.2 mg/L   | IUCLID  |

### 2-Butanone, oxime (96-29-7)

|                     |                                |           |
|---------------------|--------------------------------|-----------|
| LC50 Inhalation RAT | > 4.83 mg/L no deaths occurred | EU_CLH    |
| LD50 Dermal RABBIT  | 1000 - 1800 mg/kg              | OECD_SIDS |

# WPC-01

## RADCON 100 CLEAR

4/21/2026

|                    |             |         |
|--------------------|-------------|---------|
| LD50 Ingestion RAT | = 930 mg/kg | NLM_CIP |
|--------------------|-------------|---------|

**Skin corrosion/irritation**

**Serious eye damage/eye irritation**

**Respiratory sensitization**

**Skin sensitization**

**Carcinogenicity**

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

**Germ cell mutagenicity**

**Reproductive toxicity**

**Specific target organ toxicity - single exposure**

**Specific target organ toxicity - repeated exposure**

**Aspiration hazard**

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Chlorothalonil (1897-45-6)

|      |  |     |
|------|--|-----|
| EC50 | 0.0342 - 0. (48 h; DAPHNIAMAGNA;(daphnia magna)) | EPA |
|------|--|-----|

##### Propanol, 1(or 2)-(2-methoxyme (34590-94-8)

|      |  |        |
|------|--|--------|
| LC50 | = 1919 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna)) | IUCLID |
|------|--|--------|

##### Calcium propionate (4075-81-4)

|      |   |        |
|------|---|--------|
| EC50 | > 500 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna)) | IUCLID |
|------|---|--------|

##### 2-Butanone, oxime (96-29-7)

|      |   |        |
|------|---|--------|
| EC50 | = 750 mg/L (48 h; DAPHNIAMAGNA;(daphnia magna)) | IUCLID |
|------|---|--------|

#### 12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

#### 12.4 Mobility in soil

#### 12.5 Results of PBT and vPvB assessment

#### 12.6 Other adverse effects

#### 12.7 Additional Information

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Handling for disposal

##### Methods of disposal

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

##### Contaminated packaging

\*\* Rags, steel wool, and paper towels soaked with this product may spontaneously catch fire if improperly stored and/or discarded. Immediately after each use place rags, steel wool, and paper towels in a sealed water-filled container to prevent spontaneous combustion.

### SECTION 14: Transport Information

# WPC-01

## RADCON 100 CLEAR

4/21/2026

|  |  |
|--|--|
| <b>14.1 UN number</b>                  | NA1993   |
| <b>14.2 UN proper shipping name</b>    | NA1993,Combustible liquid, n.o.s. (contains ... Mineral Spirits), 3, PGIII |
| <b>14.3 Transport hazard class(es)</b> | 3  |
| <b>14.4 Packing group</b>              | III  |

### 14.5 Environmental hazards

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of Marpol112 and the IBC Code

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

3

#### SARA313

1897-45-6 (Chlorothalonil)

#### Inventory - United States - Section 8(b) Inventory (TSCA)

10605-21-7 (Carbendazim)

136-51-6 (Calcium 2-ethylhexanoate)

136-52-7 (Hexanoic acid, 2-ethyl-, cobal)

1897-45-6 (Chlorothalonil)

34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)

4075-81-4 (Calcium propionate)

471-34-1 (Carbonic acid, calcium salt (1)

55406-53-6 (3-Iodo-2-propynyl butylcarbama)

64742-42-3 (Hydrocarbon waxes, petroleum,)

64742-47-8 (Petroleum distillates, hydrotr)

96-29-7 (2-Butanone, oxime)

#### CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

136-52-7 (Hexanoic acid, 2-ethyl-, cobal)

#### US - CERCLA/SARA - Section 313 - Emission Reporting

55406-53-6 (3-Iodo-2-propynyl butylcarbama)

#### VOC

34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)

64742-47-8 (Petroleum distillates, hydrotr)

96-29-7 (2-Butanone, oxime)

#### US - California - Proposition 65 - Carcinogens List

1897-45-6 (Chlorothalonil)

#### Canada - Domestic Substance List (DSL)

10605-21-7 (Carbendazim)

136-51-6 (Calcium 2-ethylhexanoate)

136-52-7 (Hexanoic acid, 2-ethyl-, cobal)

1897-45-6 (Chlorothalonil)

34590-94-8 (Propanol, 1(or 2)-(2-methoxyme)

4075-81-4 (Calcium propionate)

471-34-1 (Carbonic acid, calcium salt (1)

55406-53-6 (3-Iodo-2-propynyl butylcarbama)

64742-42-3 (Hydrocarbon waxes, petroleum,)

64742-47-8 (Petroleum distillates, hydrotr)

96-29-7 (2-Butanone, oxime)

# WPC-01

## RADCON 100 CLEAR

4/21/2026

### 15.2 Chemical Safety Assessment


|                            |   |
|----------------------------|---|
| <b>HEALTH</b>              | 2 |
| <b>FLAMMABILITY</b>        | 2 |
| <b>PHYSICAL HAZARD</b>     | 1 |
| <b>PERSONAL PROTECTION</b> | X |

2 - Hazardous

2 - Above 100°F not exceeding 200°F

1-Normally stable, but can become unstable at high temperatures and pressures.

X- Ask Supervisor or Safety Specialist for Handling Instructions



### SECTION 16: Other information

N/A

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.